

3M™ Polyurethane Protective Tape 8560

Technical Data Sheet

Product Description

3M™ Polyurethane Protective Tape 8560 is an indoor-grade tape made from an abrasion-resistant polyurethane elastomer that resists puncture, tearing, abrasion, and erosion. 3M 8560 Tape is a cost-effective method for protecting a surface from corrosion, abrasion, and minor impact damage. 3M 8560 Tape is a transparent tape constructed with a pressure-sensitive, natural rubber adhesive protected with an easy-release liner.

Typical Physical Properties and Performance Characteristics

Note: 1) The following technical information and data should be considered representative or typical only and should not be used for specification purposes. 2) ASTM = American Society for Testing and Materials. 3) Metric values are listed in parenthesis

Property	Test Method	Units	Typical Value
Tensile Strength @ Break	ASTM D882	lb/in (N/100 mm)	75 (1313)
Elongation % @ Break	ASTM D882	%	400
Peel Adhesion @ 70°F (21°C) to:	ASTM D3330 Method A 24 hour dwell	oz/in (N/100 mm)	Plate Glass
Anodized Aluminum			92 (100)
Acrylic Enamel Paint			29 (31)
Mil-P-23377 Epoxy Primer			32 (35)
Max. Service Temperature		°F (°C)	180°F (82°C)

Dimensions

Approximate Applied Thickness*	0.012 inch (0.30 mm) Film 0.002 inch (0.06 mm) Adhesive 0.014 inch (0.36 mm) = Total thickness
Standard Roll Length	36 yd (32.9 m)
Available Widths	Minimum 1 inch Maximum 48 inches (2.54 cm to 122 cm)
Approximate Weight*	0.82 lb/yd ² (447 g/m ²)

*Excludes the liner that is removed from the tape prior to application.

Shipping and Storage

No special/hazardous labeling or packaging required or regulations for air, ground or water shipment for this product.

Keep film in a clean area, away from excessive moisture and out of direct sunlight. Store rolls in the shipping carton. Return partially used rolls to the shipping carton.

Shelf life: Two (2) years from date of manufacture

Additional Information

In the U.S. call toll free 1-800-235-2376, or fax 1-800-435-3082 or 651-737-2171. For U.S. Military, call 1-866-556-5714. If you are outside of the U.S., please contact your nearest 3M representative.

**These products were manufacture under a 3M Quality Management System registered to the AS9100 standard*

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information. **Product Selection and Use:** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property. **Warranty, Limited Remedy, and Disclaimer:** Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. **Limitation of Liability:** Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



Automotive & Aerospace Solutions Division
3M Center
St. Paul, MN 55144-1000
Phone 1-800-328-1684
Web www.3M.com/aerospace

8560
Issue date: 6/2018

3M is a trademark of 3M Company
© 3M 2018. All rights reserved.